

Modeling of the starter-generator device for truck KAMAZ

Gumerov A., Nasibullin R., Sarimov L.

Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

© 2016 IEEE. The generalized mathematical model of the switched-induction machine is developed. Placement of the magnetic flux in space of the electrical machine in the ANSYS Workbench program is calculated. Flux linkages dependencies on the current value and the relative angle of rotor rotation as MATLAB-functions are generalized. The simulation model of the starter-generator device is designed in the MATLAB/Simulink environment. Modeling with parameters a starter-generator device for the truck KAMAZ is carried out. The main characteristics of the work of the starter-generator device in the starter and generator modes are defined. Comparison of results of modeling with regular electric equipment of the truck is made.

<http://dx.doi.org/10.1109/ICIEAM.2016.7911695>

Keywords

flux linkage, simulation model, starter-generator device, switched-induction machine

References

- [1] R. Cardenas, W.F. Ray, G.M. Asher, "Switched reluctance generators for wind energy applications, " in Proc. Power Electronics Specialists Conference, 1995, vol. 1, pp. 559-564.
- [2] A. de Vries, Y. Bonnassieux, M. Gabsi, E. Hoang, F. d-Oliveira, Cedric Plasse, "A switched reluctance machine for a car stater alternator system, " in Proc. IEEE International Electric Machines and Drives Conference 2001, pp.323-329.
- [3] Gabriel Gallegos-Lopez, James Walters, Kaushik Rajashekara, "Switched Reluctance Machine Control Strategies for Automotive Applications, " in Proc. SAE World Congress, March 2001.
- [4] David A. Torrey, "Switched Reluctance Generators and Their Control, " IEEE Transactions on industrial electronics, vol. 49, no. 1, February 2002.
- [5] Erkan Mese, Yilmaz Sozer, James M. Kokernak, Dvid A. Torrey, "Optimal Exitation of a High Speed Switched Reluctance Generator, " in Proc. Applied Power Electronics Conf and Exhibition (APEC), IEEE 2000, vol. 1, pp. 362-368.
- [6] R. Krishnan, Switched reluctance motor drives: modeling, simulation, analysis, design and applications, CRC Press, 2001.
- [7] T.J.E. Miller, Switched Reluctance Motors and Their Control. Oxford University, 1993.
- [8] V.V. Nikolaev, V.A. Rybnikov, "Development of an Integrated Starter-Generator on the Basis of a Machine, " Electricity, no. 5, pp. 32-38, 2005.
- [9] S.G. Buryakovsky, B.G. Lubarsky, A.D. Petrushin, A.S. Masliy, "Mathematical modeling of gate-inductor motor to drive the turnout, " Electrotechnic and computer systems, no. 3, pp. 157-158, 2011.

- [10] B.G. Lubarsky, E.S. Ryabov, L.V. Overianova, V.L. Emeljanov, "A simulation model of a traction valve inductor electric drive, " *Electrical Engineering and Electromechanics*, no. 5, pp. 67-72, 2009.
- [11] R.I. Valiev, A.Z. Gumerov, A.N. Murtazin, R.T. Nasibullin, R.Sh. Sadriev, A.A. Khafizov, "Integrated starter/alternator device for trucks KAMAZ-5308, " *Scientific and Technical Volga region Bulletin*, no. 5, pp. 130-133, 2013.
- [12] Starter-generator mit Asynchronmaschine und feldorientierten Regelung, *Automobiltechn. Z.* 2000, no 1, Sonderausg, *Automot. Electron.*
- [13] F. Henrotte, G. Deliege, K. Hameyer, "The eggshell method for the computation of electromagnetic forces on rigid bodies in 2D and 3D, " in *Proc. CEFC 2002*, Perugia, Italy, April 16-18, 2002.
- [14] S. McFee, J.P. Webb, D.A. Lowther, "A tunable volume integration formulation for force calculation in finite-element based computational magnetostatics, " *IEEE Transactions on Magnetics*, 24(1), pp. 439-442, January 1988.